



NICE Uptivity External Cumulative Release Notes 18.1.1

TOC

- Release Notes for NICE Uptivity 18.1.1 1
 - Release Build Information 1
 - Obtaining the Release Software 1
- Customer Site Requirement Changes for the 18.1.1 patch 2
 - Server Hardware 2
 - Server Software 2
 - User Workstation/PC 2
 - Database Changes 2
 - Licensing 2
 - Security 2
- Major Features and Enhancements in the 18.1.1 patch 3
 - Blackouts 3
 - CXone: Multi-site Support for Media Playback 3
 - Speech Analytics: Multi-site 3
 - Speech Analytics: Phonetic Index Retention 4
 - Screen Recording: Retention Management 4
 - Screen Recording: Mouse Pointer Capture 4
 - Web Portal: Internationalization 4
 - Transcoder 2 Setting 5
- Technical Documentation Enhancements with 18.1.1 6
 - Help Site 6
- 18.1 External Release Notes 7**

NICE Uptivity External Cumulative Release Notes

- **Version** – 18.1.1
- **Release Date** – July 2019
- **Last Revision** – October 2019
- **Copyright** – ©2019 NICE inContact
- **Disclaimer** – NICE inContact reserves the right to update or append this document, as needed.

Release Notes for NICE Uptivity 18.1.1

This guide introduces the changes to Uptivity in the 18.1.1 patch.

Release 18.1.1 is a patch to Release 18.1 intended to address critical issues, restore several screen capture features present in previous releases, and address several high priority screen recording and speech analytics enhancements.

Release Build Information

Initial Build Version – 18.11.0824.27

Release Date – August 31, 2018

Obtaining the Release Software

Uptivity software must be obtained and installed through the Uptivity Installation team. Software and services are only available to customers who have a current maintenance contract.

To learn more about upgrading to this release, contact your Uptivity Account Manager.

Customer Site Requirement Changes for the 18.1.1 patch

Note:

This section discusses **only** those site requirements that have changed in this patch of NICE Uptivity. For complete information regarding site requirements, see the appropriate customer site requirements guide for your deployment model and the appropriate customer guide(s) for recording integrations, workforce management integrations, or both.

Server Hardware

There were no server hardware changes in 18.1.1.

Server Software

Web servers hosting the NICE Uptivity Web Portal require .NET framework v4.7.2.

User Workstation/PC

User workstations must use .NET 4.7.2.

Database Changes

There were no database changes in 18.1.1.

Licensing

There were no licensing changes in 18.1.1.

Security

There were no security changes in 18.1.1.

Major Features and Enhancements in the 18.1.1 patch

For additional information, see the technical documentation references cited for each feature or ask your NICE Uptivity representative.

Blackouts

Real-Time Blackouts is the only supported blackout method within NICE Uptivity going forward. This blackout method provides the highest level of security because it prevents sensitive information from ever being recorded. For integrations that provide a completed recording to Uptivity, such as ShoreTel TAPI-WAV, Post-Call Blackouts are still acceptable. In this scenario, the audio is transcoded just to apply the blackout.

All [API Server Commands](#) continue to be supported; however, due to Real-Time Blackouts being the only supported method of blackouts, any value specified for OFFSET in an API command is no longer used as they were specific to Post-Call Blackouts.

CXone: Multi-site Support for Media Playback

The initial release of the Uptivity-CXone WFO Pro integration supported media playback from a single media archive only. For version 18.1.1, the Uptivity-CXone integration now supports multiple media archives that are distributed across separate sites. (A site is a physical location where media is archived.)

Multi-site support eliminates media file "round-tripping" for users that are playing back media in the same location that the media is stored. By eliminating media file round-tripping, less network bandwidth is used, which optimizes system performance.

Note:

"Round-tripping" is when a file is routed across a network to a non-local site (for some function or service) and is then re-routed back to its local site. Round-tripping usually occurs in some form of a centralized system.

Documentation with further details and instructions is in progress and will be available, linked from here, by the release date.

Speech Analytics: Multi-site

NICE Uptivity supports the coordination of multiple Speech Analytics servers located across geographically-separate sites. An advantage of this capability is that media files can be processed locally, eliminating the need to send large media files across a WAN to be processed at a different site.

Speech Analytics: Phonetic Index Retention

Each call processed by Uptivity Speech Analytics creates a phonetic index - a file that is stored on the analytics server and managed by Nexidia. The phonetic index is kept to facilitate anticipated functionality that will allow searching for calls that have previously gone through analytics processing.

18.1.1 includes a process to delete indexes after a configurable number of days for disk space management. The **PAT Retention Days** setting on the Analytics Module Configuration page in the Web Portal determines, in days, how long a PAT is kept. If the multi-site analytics feature described previously is being used, this value affects all analytics processing servers.

Screen Recording: Retention Management

In version 18.1, the recording storage standard changed from using separate files for the audio and video of a recording to using an industry-standard media container file (WebM) that stores audio and video together. This new file format reduced the amount of space needed for archiving recordings by an average of 80%, facilitated responsive and resource friendly playback in web browsers without use of plug-ins such as Silverlight, and also enabled the Uptivity to CXone WFO Pro integration.

Because WebM is a combined file format, 18.1 was missing the historical Uptivity feature known as archive actions. Archive actions allow video to be removed from an audio + video recording. This capability has been restored in the 18.1.1 release, and is configured with the same archive actions used in 17.3 and earlier releases. For customers upgrading from 17.3 to 18.1.1, existing archive actions will continue to work without any change.

Screen Recording: Mouse Pointer Capture

In 18.1, screen recordings did not include the user's mouse pointer. Screen recordings in 18.1.1 add the mouse pointer back to each frame used to create the video. The inclusion of the mouse pointer is not configurable. There is no animation of the mouse pointer as it moves across the screen.

For customers migrating from 17.3 or earlier releases to 18.1.1, the retranscoding of existing videos will keep the mouse pointer.

Web Portal: Internationalization

Web Portal has been updated to facilitate localization. The following languages are available in 18.1.1:

- French Canadian
- Hebrew
- German
- European French
- North American Spanish

- Brazilian Portuguese
- Castilian Spanish

There are a few specific considerations regarding localization in Uptivity:

- The base Web Portal application is multi-lingual. The language displayed to the end user is determined by available translations of the Web Portal and the locale settings of the user's computer and web browser.
- Reports are uni-lingual and use US formats for dates, times and numbers. The language that reports are presented in is determined upon installation.
- Performance Management and its ACD Reporting are not currently localizable and thus remain in US English only. There are currently no plans to localize Performance Management.

Transcoder 2 Setting

There is a new setting in the Transcoder 2 service INI file. The setting configures the number of concurrent video transcoding threads that the system can process.

Technical Documentation Enhancements with 18.1.1

This topic introduces the changes, additions, and improvements to technical documentation for NICE Uptivity since the release of the previous version.

Help Site

- A brand new, modern design has been implemented site-wide.
- The menu options have been rearranged so that each topic falls under the user role who would need the information - Administrator, Supervisor, or Agent.



NICE Uptivity External Release Notes

18.1

NICE Uptivity External Release Notes

- **Version** – 18.1
- **Release Date** – May 2, 2018
- **Last Revision** – September 2018
- **Copyright** – ©2018 NICE inContact Inc.
- **Disclaimer** – NICE inContact reserves the right to update or append this document, as needed.

Release Notes for NICE Uptivity 18.1

This guide introduces the changes to Uptivity since the release of 18.1.

Release Build Information

Initial Build Version – 18.1.0427.18

Release Date – May 2, 2018

Obtaining the Release Software

Uptivity software must be obtained and installed through the Uptivity Installation team. Software and services are only available to customers who have a current maintenance contract.

To learn more about upgrading to this release, contact your Uptivity Account Manager.

Customer Site Requirement Changes for 18.1

Note:

This topic discusses **only** those site requirements that have changed since the previous version of NICE Uptivity. For complete information regarding site requirements, see the appropriate customer site requirements guide for your deployment model and the appropriate customer guide(s) for recording integrations, workforce management integrations, or both.

Server Hardware

Hardware requirements vary depending on the deployment model, telephony integration, Uptivity components used, and number of concurrent users in the system.

- Your server must have at least 4 Cores and 12GB of RAM dedicated to Uptivity.
- Hardware requirements used by Sales Engineering were revised mid-2017. This information can be found in the document *Minimum Server Specification Guidelines*.

Server Software

- 32-bit and 64-bit Microsoft Visual C++ Redistributable for Visual Studio 2017 must be installed on all Uptivity servers (in addition to libraries required in previous versions).
- Web servers hosting the NICE Uptivity Web Portal require .NET framework v4.7.1.
- No changes in server OS for 18.1.
- No changes to SQL requirements for 18.1.

User Workstation/PC

Note:

When a system includes NICE Uptivity Screen Recording, Desktop Analytics, or both, consult Uptivity Sales Engineering for recommended system requirements based on business needs.

- 32-bit and 64-bit C++ libraries for 2010 and 2017 are required on user workstations in addition to libraries required in previous versions.
- User workstations must use .NET 4.7.1.
- Microsoft Silverlight no longer needs to be installed as it is no longer used in Uptivity.
- For screen capture, communication between the User Workstation and the RabbitMQ server require out-bound TCP activity on ports 5672.

- **Internet Explorer 11** – Internet Explorer version 11 remains supported by NICE Uptivity 18.1 with limitations:
 - Live Monitor is not available using IE 11.
 - At the end of a recording, the playhead indicator does not reset at the beginning of the recording.
 - When a user closes the Screen pane and the Layer Details pane, the Waveform Display maximizes to the full screen size.
 - When using either the Waveform Display or the Seek icon, the user must click the Play icon to continue playing the call.
 - If a user changes the playback speed, the Waveform Indicator appears beyond the total duration time in the Playback Details pane.

NICE Uptivity 18.1 is expected to be the last NICE Uptivity release to officially support the use of Internet Explorer.

Warning:

Due to some functionality that is not compatible with the Internet Explorer 11 browser, we do not recommend using IE 11 with Uptivity 18.1.

Database Changes

There was a material change to track which calls have been uploaded to CXone.

Licensing

There are no licensing changes for NICE Uptivity 18.1.

Security

There are no security changes for version 18.1.

Major Features and Enhancements in 18.1

For additional information, see the technical documentation references cited for each feature or ask your Uptivity representative.

CXone WFO Pro Integration

With this release, the call and desktop recording capabilities of Uptivity can now be used as voice and screen connectors for CXone WFO Pro, creating a hybrid (premise and cloud) workforce optimization solution.

Through the integration, CXone WFO Pro stores a copy of all recording metadata and accesses recording media that is stored on premise, allowing users to playback recordings and perform quality management tasks from CXone WFO Pro.

For more information, see [CXone WFO Pro Integration](#).

New Screen Capture Solution

Uptivity's Screen Capture solution has been thoroughly redesigned to support the integration with CXone WFO Pro and to bring greater value to customers by reducing space required for storing screen recordings.

Uptivity now utilizes the WebM open file format for storing screen capture and audio media files - a call recording and its screen recording are combined into a single media file. By adopting WebM as the standard media file format, Uptivity call media is now compatible with CXone WFO Pro.

Additionally, leveraging WebM as the standard media file format brings several significant benefits to a customer's Uptivity system:

- Up to an 80% reduction in disk space used for systems that are recording audio and video media together.
- Reduced network bandwidth between desktops and server. This performance gain is a result of compressing the desktop images that are captured during screen recording before sending them to the server.
- Use of an open file format for archived recordings, instead of the legacy proprietary format, removes the dependency on Silverlight for all media playback.

For more information about NICE Uptivity Screen Capture, see [NICE Uptivity Screen Recording Overview](#).

Functionality Changed or Removed

Important changes to Uptivity functionality:

Silverlight

- The Web Player (Silverlight Player) is no longer available. All recording playbacks use the HTML5 Interaction Player. The Web Player was removed as a result of Microsoft's obsolescence of Silverlight.

- Silverlight Live Monitor, Silverlight Call List, and the Web Media Server service have been deprecated as they are no longer required.

HTML5 Interaction Player

- All call and screen recording playback is through the HTML5 Interaction Player.
- The HTML5 Interaction Player in 18.1 provides an improved playback experience from previous versions. It features improved performance, reduced memory and resource usage, support for playback of larger and longer recordings, and playback speed control.
- The following features are not available in the HTML5 Interaction Player:
 - Display of the cursor in screen recordings.
 - Ability to apply manual blackouts to recordings.

Transcoder

- The **Transcode by Board** setting has been removed. This setting specified whether the voice board ID should be added as a prefix to the Transcoder record for each call.
- The **Look for Code** field on the Transcoder configuration page relates to the **Transcode by Board** setting, so it has also been removed.
- **Settings Removed from the Transcoder Configuration Page** – In addition to the **Look for Code** field mentioned above, the following settings have also been removed from the Transcoder Configuration Page due to the transcoder redesign: **Create Analytics**, **Analytics Keep Days**, **Analytics Storage Path**.

Archiver

- The **Archive Restriction** setting has been removed from the **New Archive Action** and **Edit Archive Action** pages. The Archive Restriction setting specified which recording-related files should be governed by the archive action (audio, video, analytics).
- This setting was removed because the **Archiver** in version 18.1 is unable to archive or purge audio and video files separately (for media files that contain both audio and video).

Media Export

- Uptivity users cannot export media files in the following file formats in version 18.1:
 - .WAV
 - .CAV
 - .VOX
 - .MP3
- Media files can only be exported as a WebM file for version 18.1.

Blackouts

- Uptivity no longer supports:
 - Call-level blackouts
 - Manual / Agent-level transcoded blackouts for video
- Uptivity continues to support:
 - Manual / Agent-level transcoded blackouts for audio
 - Real-time blackouts for video
- For more information about blackouts, see [Blackouts Overview](#).

Timed Schedules

- Timed schedules are no longer supported.

Workstation Mapping No Longer Supported

- Screen recording by statically mapping a phone extension or device to a Windows workstation name is no longer supported. Each agent must use a dedicated Windows login.
- Windows usernames must be unique for every Uptivity system username.
- If users at a company have accounts with more than one domain, during user profile configuration, the complete domain name that users will use to log in to their workstation that will be recorded must be specified.

Technical Documentation Enhancements for 18.1

This topic introduces the changes, additions, and improvements to technical documentation for NICE Uptivity since the release of the previous version:

- Written references to the Call List have been removed. The Call List was used with the Web (Silverlight) Player, which is no longer a part of the product as of this release. Instead, the Recorded Interactions List plays in the HTML5 Interaction Player.
- Information for installing new prerequisites and installing and configuring the Screen Capture API (SCAPI) and Transcoder 2 has been added to the Installation Guide.